

BS EN3 CO2 Type Fire Extinguisher

PRESSURE EQUIPMENT DIRECTIVE
APPROVED FIRE EXTINGUISHERS



0038/03

MARINE EQUIPMENT DIRECTIVE
APPROVED FIRE EXTINGUISHERS



0038/03



CERTIFIED TO BS EN3
LICENCE NO. KM 57533



Quality
Endorsed
Company

ISO 9001:2000




FEX180

FEX182

FEX181

FEX183



- British Standards Institution – BSI approval.
- Suitable for Class B & Electrical Hazards.
- High quality and good value.
- Colour coded for instant recognition.
- Available in aluminium and light weight steel.
- Easy to use and leave no messy residue.
- ISO 9001 Certified Quality System by QAS Australia.

TECHNICAL SPECIFICATION

	2kg	5kg	2kg	5kg
EXTINGUISHER TYPE				
MATERIAL	Steel	Steel	Aluminium	Aluminium
MODEL NO.	FEX182	FEX183	FEX180	FEX181
FIRE RATING	34B	55B	34B	55B
OPERATING TEMPERATURE	-20°C to 60°C			
OPERATING PRESSURE	50 Bar at 20°C			
CYLINDER SPECIFICATION	1997/23/EC			
HEIGHT	625mm	770mm	575mm	695mm
FULL WEIGHT	8.4kg	15.8kg	6.1kg	15.2kg
EMPTY WEIGHT	6.4kg	10.8kg	4.1kg	10.2kg
DISCHARGE TIME	14 secs	15 secs	14 secs	15 secs
RANGE OF THROW (approx)	4 - 5 M	4 - 5 M	4 - 5 M	4 - 5 M
CARTON SIZE mm	220 x 180 x 650	230 x 245 x 780	180 x 200 x 530	230x 240 x 720

* Pending approval.

The products specified in this brochure are subject to continual development and improvement. Information in this brochure is subject to alteration without notice. All dimensions in mm unless otherwise specified.