

BS EN3 Water & Foam Type Fire Extinguisher

PRESSURE EQUIPMENT DIRECTIVE
APPROVED FIRE EXTINGUISHERS



0038/03

MARINE EQUIPMENT DIRECTIVE
APPROVED FIRE EXTINGUISHERS



0038/03



CERTIFIED TO BS EN3
LICENCE NO. KM 57533




Quality
Endorsed
Company

ISO 9001:2000



- British Standards Institution – BSI approval.
- Foam type is suitable for Class A & B.
- Water type is suitable for Class A.
- Protective plastic lining.
- Colour coded for instant recognition.
- High quality and good value.
- ISO 9001:2000 Certified System by QAS Australia.



TECHNICAL SPECIFICATION

EXTINGUISHER TYPE	6L	2L	9L	9L	9L	9L
	FOAM	FOAM	FOAM	WATER	FOAM	WATER
	STORE PRESSURE TYPE (NITROGEN PROPELLENT)			CO2 CARTRIDGE		
MODEL NO.	FEX102	FEX116	FEX103	FEX101	FEX112	FEX111
FIRE RATING	13A, 144B	5A, 34B	21A, 183B	13A	13A, 183B	13A
OPERATING TEMPERATURE	0°C to 60°C					
OPERATING PRESSURE	12 Bar					
TEST PRESSURE	25 Bar					
HEIGHT	555mm	400mm	625mm	625mm	630mm	630mm
FULL WEIGHT	9.2kg	4.0kg	13.5kg	13.5kg	14.2kg	14.2kg
DISCHARGE TIME	50 secs	12 secs	65 secs	61 secs	94 secs	89 secs
RANGE OF THROW (approx)	4 - 5 M	2 M	4 - 5 M	6 M	4 - 5 M	6 M
CARTON SIZE mm	190 x 210 x 565	125 x 160 x 430	200 x 200 x 646	200 x 200 x 645	200 x 200 x 645	200 x 200 x 645