

获得中国船级社/MED认证的救生圈灯 SELF-IGNITING LIGHT CERTIFIED BY CCS / MED

- 耐腐蚀
- 耐高温低温
- 承受更高抛落高度
- 防震 防霉 易操作
- 符合海事组织SOLAS及其修正案
- CORROSION RESISTANCE
- HIGH AND LOW TEMPERATURE RESISTANCE
- WITHSTAND HIGHER DROP
- SHOCK PROOF, MOULD PROOF AND EASY TO OPERATE
- SOLAS, AS AMENDED



LED光源
LED lamp holder



水密结构
Watertight structure



牢固外壳
Secure housing



方便开关
Convenient switch



救生圈灯系绳
Life buoy light tether

产品性能 PRODUCT PERFORMANCE





救生圈自亮灯FBQD2

EXPLOSION PROOF LIFEBOUY SELF-IGNITING LIGHT FBQD2

(本安型防爆)

(INTRINSIC SAFETY TYPE)

扫码观看产品视频
PRODUCT VIDEOLED光源
LED
LIGHT SOURCE耐高低温
WITHSTAND HIGH
AND LOW TEMPERATURE防水
WATER
PROTECTION防爆本安
EXPLOSION PROOF
INTRINSIC SAFETY防震
SHOCK
PROOF可换电池
REPLACEABLE
BATTERY

产品参数

- 符合1974 SOLAS及其最新修正案;
符合IEC60079-0;IEC60079-11
- 控制方式:方向开关
- 使用光源:LED (闪光)
- 可更换电池: 2*LR20碱性电池
- 防爆等级:Ex ia II C T4
- 外形尺寸:Φ100mm*295mm
- 重量:700g

产品编码	30602008	30602009
产品认证		

PRODUCT PARAMETERS

- SOLAS, as amended,
IEC60079-0; IEC60079-11
- Activation: Self-activated by tilt-switch
- Light type: Flashing LED
- Replaceable battery: 2*LR20 Alkaline battery
- Explosion proof level: Ex ia II C T4
- Size: Φ100*295mm
- Weight: 700g

ITEM CODE	30602008	30602009
Approval		

救生圈自亮灯HYQD20

LIFEBOUY SELF-IGNITING LIGHT HYQD20

扫码观看产品视频
PRODUCT VIDEO不锈钢支架可选
Stainless steel
bracket optionalLED光源
LED
LIGHT SOURCE耐高低温
WITHSTAND HIGH
AND LOW TEMPERATURE防水
WATER
PROTECTION防震
SHOCK
PROOF可换电池
REPLACEABLE
BATTERY

产品参数

- 符合1974 SOLAS及其最新修正案;
- 控制方式:方向开关
- 使用光源:LED (闪光)
- 可更换电池: 2*LR6 (5#碱性电池)
- 发光时间:≥2h
- 发光强度:≥2cd
- 外形尺寸:Φ83mm*248mm
- 圈灯重量:191g (不含电池、安装架)
- 安装支架:塑料、不锈钢

产品编码	30602020	30602019
产品认证		

PRODUCT PARAMETERS

- SOLAS, as amended,
Activation: Self-activated by tilt-switch
- Light type: Flashing LED
- Replaceable battery: 2*LR6 Alkaline battery
- Flashing duration: ≥ 2 hours
- Flashing intensity: ≥ 2 cd
- Size: Φ83mm*248mm
- Weight: 191g (Without battery and bracket)
- Bracket: Plastic, stainless steel

ITEM CODE	30602020	30602019
Approval		

救生圈自亮灯 QD10G

LIFEBUOY SELF-IGNITING LIGHT QD10G



碱性电池
Alkaline battery



扫码观看产品视频
PRODUCT VIDEO



LED光源
LED LIGHT SOURCE



耐高低温
WITHSTAND HIGH AND LOW TEMPERATURE



防水
WATER PROTECTION



防震
SHOCK PROOF



方便开关
CONVENIENT SWITCH



不可换电池
NON REPLACEABLE BATTERY

产品参数

- 符合1974 SOLAS及其修正案
- 控制方式:插销开关
- 使用电源:碱性电池
- 使用光源:LED (闪光)
- 发光时间:≥2h
- 发光强度:≥2cd
- 外形尺寸:Φ75mm*158mm
- 重量:122g

产品编码	30602010	30602011
产品认证		

PRODUCT PARAMETERS

- SOLAS,as amended
- Activation:Latch switch
- Battery type:Alkaline battery
- Light type:Flashing LED
- Flashing duration:≥ 2 hours
- Flashing intensity:≥ 2 cd
- Size:Φ75mm*158mm
- Weight:122g

ITEM CODE	30602010	30602011
Approval		

救生圈自亮灯 QD10L

LIFEBUOY SELF-IGNITING LIGHT QD10L



锂电池
Lithium battery



扫码观看产品视频
PRODUCT VIDEO



LED光源
LED LIGHT SOURCE



耐高低温
WITHSTAND HIGH AND LOW TEMPERATURE



防水
WATER PROTECTION



防震
SHOCK PROOF



方便开关
CONVENIENT SWITCH



不可换电池
NON REPLACEABLE BATTERY

产品参数

- 符合1974 SOLAS及其修正案
- 控制方式:插销开关
- 使用电源:锂电池
- 使用光源:LED (闪光)
- 发光时间:≥2h
- 发光强度:≥2cd
- 外形尺寸:Φ75mm*158mm
- 重量:107g

产品编码	30602012	30602013
产品认证		

PRODUCT PARAMETERS

- SOLAS,as amended
- Activation:Latch switch
- Battery type:Lithium battery
- Light type:Flashing LED
- Flashing duration:≥ 2 hours
- Flashing intensity:≥ 2 cd
- Size:Φ75mm*158mm
- Weight:107g

ITEM CODE	30602012	30602013
Approval		